

UNCLASSIFIED

AD 410203

DEFENSE DOCUMENTATION CENTER

FOR

SCIENTIFIC AND TECHNICAL INFORMATION

CAMERON STATION, ALEXANDRIA, VIRGINIA



UNCLASSIFIED

NOTICE: When government or other drawings, specifications or other data are used for any purpose other than in connection with a definitely related government procurement operation, the U. S. Government thereby incurs no responsibility, nor any obligation whatsoever; and the fact that the Government may have formulated, furnished, or in any way supplied the said drawings, specifications, or other data is not to be regarded by implication or otherwise as in any manner licensing the holder or any other person or corporation, or conveying any rights or permission to manufacture, use or sell any patented invention that may in any way be related thereto.

CATALOGED BY DDC 410203
AS AD No.

The views, conclusions, or recommendations expressed in this document do not necessarily reflect the official views or policies of agencies of the United States Government.

This document was produced by SDC performance of contract AF 04 (695)-40
1/4

TECH MEMO



a working paper

System Development Corporation / 2500 Colorado Ave. / Santa Monica, California

DDC AVAILABILITY NOTICE

QUALIFIED REQUESTERS MAY OBTAIN COPIES OF THIS REPORT FROM DDC.
Proposal for Variable Field Definition Pseudo Operation
in LARII

TM-890/002/00

AUTHOR *F. J. LaChapelle*
F. J. LaChapelle

TECHNICAL *J. B. Munson*
J. B. Munson

RELEASE *T. C. Tennant*
T. C. Tennant

for S. Rothman

DATE PAGE 1 OF 4 PAGE


19 December 1962

A variable Field Definition (VFD) pseudo will generate one or more words of data made up of one or more subfields.

The constituents of a VFD pseudo operation would be a VFD in the operation field and one or more subfields in the M-term. If a symbol appears in the location field the tag would be assigned to the location of the first word generated.

Seven types of subfields would exist:

- 1) M-term
- 2) Octal
- 3) Decimal
- 4) Hollerith
- 5) Flexowriter
- 6) Teletypewriter
- 7) Literal



The format of a subfield is:

1. The number of bits of data this subfield is to generate. This is specified by an unsigned decimal integer between one and ninety-six.
2. A single letter to specify the type of information given by the subfield. This letter follows the decimal integer.

The letter "M" specifies an M-term format subfield.
The letter "B" specifies an Octal format subfield.
The letter "D" specifies a Decimal format subfield.
The letter "H" specifies a BCD format subfield.
The letter "F" specifies a FLX format subfield.
The letter "T" specifies a TEL format subfield.
The letter "L" specifies a Literal format subfield.

The letter is followed by a slash "/", and the actual data subfield is contained between this slash and the first blank or comma (whichever is encountered first). In the case of a comma, another subfield begins immediately following the comma. A blank terminates the VFD pseudo op M-term.

The type of information given following the slash depends on the letter:

1. In the case of an M, the data item consists of any legal symbolic M-term expression (except a literal).
2. In the case of a B, the data item consists of a legal M-term for the OCT pseudo operation.
3. In the case of a D, the data item consists of a legal M-term for the DEC pseudo operation.
4. In the case of an H, F, or T, the data item consists of a legal M-term for the BCD, FLX, or TEL pseudo operations respectively, except that no character can be a comma or a blank. A word count cannot be specified.
5. In the case of an L, the data item consists of a legal literal subfield. If the literal is of the M-term type, it must contain a comma to specify upper and lower addresses of the literal word (even if one is zero) unless it is the last subfield in the VFD.

Any number of subfields may be used.

The subfields are taken in order and are left justified. A subfield may take up more than one word. If the bit count for the first subfield is 50, the first 48 bits would go in word one, and the last two bits in Bit 47 and Bit 46 of word two. This procedure applies independent of the starting place of the subfield. One subfield may require up to three words to contain it. Each subfield is exactly the length of its bit count, regardless of the number of bits required to generate the data item. If the total number of bits in all subfields is not a multiple of forty-eight, the low order bits of the last word are filled out with zeros.

M-term data items

The data item in a M-term subfield is evaluated as if it were a standard M-term, but without cognizance of literals (a "C" error will be flagged if the character "=" exists in this data item, see TM-849/000/00). Let the specified bit count be n. If the data item just generated is less than n bits in length, it will be right adjusted in an n bit field, with enough leading zeros to make an n bit byte. The n bits are packed in the manner described above. If the data item is greater than n bits in length, only the rightmost n bits are used. Neither of these conditions is regarded as an error. If the data item generated is a relocatable expression, then the subfield must be so situated with respect to other subfields that its rightmost bit falls in Bit 0 or Bit 24 of a word. Further, the bit count must be fifteen or more. If this environment is not supplied, a relocation error will be flagged.

Octal data items

An Octal subfield data item may consist of any valid M-term for the OCT pseudo operation. Let n be the bit count for the subfield. If the data item as generated occupies less than n bits, sufficient zeros are placed to the left of the value to form an n bit subfield. If the data item occupies more than n bits, only the rightmost n bits are used. These conditions will not be flagged as errors.

Decimal data items

A Decimal subfield data item may consist of any valid M-term for the DEC pseudo operation. After the value is generated, it is treated exactly the same as an octal subfield.

Hollerith data item

The data item in a Hollerith subfield consists of a string (up to sixteen) of legal BCD characters, none of which is a comma or a blank. Let n be the bit count for the subfield. If the data item generated is longer than n bits, only the rightmost n bits are used. If it is less than n bits, sufficient blanks are placed to the left of the value to form an n bit subfield. If the bit count is not a multiple of six, then the leftmost blank has its left bits truncated. The bit count will not be flagged as an error in either case.

Flexowriter data items

The data item of a FLX subfield is converted as the M-term of a FLX pseudo op. There can be up to 16 characters not counting the minus zeros. Minus zero retains its meaning (shift mode), but none of the characters can be a comma or a blank. Let n be the bit count. If the data item generated occupies more than n bits, only the rightmost n bits are used. If it occupies fewer than n bits, sufficient blanks (flexowriter code for blanks) are placed to the left of the value to create an n bit subfield. Truncation of the leftmost blank follows the same rules as in the case of Hollerith data items. None of these conditions will be flagged as an error.

Teletypewriter data items

The data item of a TEL subfield is converted as the M-term of a TEL pseudo operation. The same rules apply as in the case of the Flexowriter data item.

Literal data items

The data item in a Literal subfield consists of a type letter followed by the literal data item. There are two special cases with literals. An octal

19 December 1962

-4-
(last page)

TM-890/002/00

literal has its type letter (B) at the end and a decimal literal has none at all. The same values apply here also. (See TM-849/000/00 for literals and their types.) The appearance of this type of subfield directs the assembler to generate a data item according to the rules governing literal subfields, and to then let the subfield in the VFD instruction be the location of the literal just generated. This subfield will be relocatable if the program is relocatable. The bit count for a literal subfield must be fifteen or more. Further, the rightmost bit of the subfield must fall in Bit 0 or Bit 24 of a word. A violation of either of these rules will be flagged as a relocation error, even if the program is absolute. If the bit count is greater than fifteen, the leftmost bits are filled with zeros. This is not flagged as an error.

The element asterisk may be used in an M-term subfield or an M-term literal, within a literal subfield. The value assigned to the asterisk in both cases is the location of the word which contains the leftmost bit of the VFD subfield when it is assigned. The remainder of this subfield may be in the next word (or the next two words), but the first word is always chosen.

Examples:

```
START  VFD  6H/A,3B/5,15M/A+10B
A       VFD  60H/ ABCDEF*GHI
        VFD  24L/15B,24D/10
        VFD  24L/HABCD ,24L/512
```

These would generate the following words, assuming START is at cell 10000.

10000	61	5	10011	00	0	00000
10001	20	6	16263	64	6	56667
10002	70	7	10000	00	0	00000
10003	00	0	20000	00	0	00012
10004	00	0	20001	00	0	20002
.						
.						
.						
20000	00	0	00000	00	0	00015
20001	61	6	26364	20	2	02020
20002	00	0	00000	00	0	01000

Literals at end of program.

19 December 1962

TM-809/002/00

Distribution List
External

Space Systems Division
(Contracting Agency)
Major C. R. Bond (SSOCD)

6594th Aerospace Test Wing
(Contracting Agency)
Lt. Col. A. W. Dill (TWRD)
Lt. Col. M. S. McDowell (TWRU)
TWACS

PIR-E1 (Lockheed)
N. N. Epstein
C. H. Finnie
H. F. Grover
H. R. Miller
W. E. Moorman
461 Program Office
698EK Program Office

PIR-E2 (Philco)
J. A. Bean
J. A. Isaacs
R. Morrison
W. W. Yenney

PIR-E3 (LFE)
D. F. Criley
K. B. Williams (5)

PIR-E8 (Mellonics)
F. Druding

PIR-E5 (Aerospace)
R. D. Brandsberg
R. V. Bigelow
G. J. Hansen
C.S. Hoff
T. R. Parkin
E. E. Retzlaff
R. G. Stephenson
V. White

PIR-E4 (GE-Santa Clara)
D. Alexander

PIR-E4 (GE-Sunnyvale)
J. Farrentine
N. Kirby

PIR-E4 (GE-Box 8555)
J. S. Brainard
R. J. Katucki
J. D. Selby

PIR-E4 (GE-Philadelphia)
J. F. Butler
H. D. Gilman

PIR-E4 (GE-Bethesda)
A. Pacchioli

PIR-E4 (GE-Box 8661)
J. D. Rogers

PIR-E7 (STL)
A. J. Carlson (3)

19 December 1962

TM-890/002/00

Distribution List
Internal
cont.

<u>NAME</u>	<u>ROOM</u>	<u>NAME</u>	<u>ROOM</u>
Padgett, L. A.	24085	Sweeney, M. J.	24057
Patin, O. E.	Sunnyvale	Taber, W.	22053
Polk, T. W.	24099	Tennant, T. C.	27024
Pruett, B. R.	24073	Testerman, W. D.	14032
Rabin, M.	14032	Thompson, J. W.	22077
Reilly, D.	24085	Thornton, R. L.	14032
Remstad, C. L.	27029	Totschek, R. A.	22099
Rosenberg, E. J.	14054	Vorhaus, A. H.	24082A
Rothman, S.	22116A	Wagner, I. T.	22078
Russell, R. S.	14054	West, G. D.	24114
Salisbury, L. W.	14039	West, G. P.	24094
Scott, R. J.	24090	Wilson, G. D.	22101
Seacat, C. M.	Sunnyvale	Winsor, M. E.	24137
Seiden, H. R.	22091A	Winter, J. E.	24097
Shapiro, R. S.	25026	Wise, R. C.	24051
Skelton, R. H.	24127A	Wong, J. P.	Sunnyvale
Solomon, J.	24053	Zubris, C. J.	22070
Speer, N. J.	24081		
Stone, E. S.	22116B		

19 December 1962

TM-890/002/00

Distribution List

Internal

<u>NAME</u>	<u>ROOM</u>	<u>NAME</u>	<u>ROOM</u>
Allen, R. W.	22109A	Haake, J. W.	24120
Allfree, D.	22076	Harris, E. D.	24083
Alperin, N. I.	24116	Henley, D.E.	24058B
Armstrong, E.	24089	Henry, T. R.	24061
Bernards, R. M.	Sunnyvale	Hill, C. L.	24057
Biggar, D.	24091	Hirschfield, G. A.	22113A
Black, H.	14032	Holmes, M. A.	22079
Blum, M.	24086	Holzman, H. J.	22096B
Brenton, L.	22082	Houghton, W. H.	22073
Burke, B. E.	24076	Hoyt, R. L.	14032
Busch, R. E.	24065B	Imel, L. E.	14032
Carter, J. S.	27032	Kastama, P. T.	24053
Champaign, M. E.	24127B	Kayser, F. M.	25026
Chiodini, C. M.	24075	Keddy, J. R.	24026
Ciaccia, B.	24082A	Key, C. D.	24123
Cline, B. J.	24097	Keyes, R. A.	24034
Cogley, J. L.	24135	Kinthead, R. L.	24071
Conger, L.	22076	Kneemeyer, J. A.	24065A
Cooley, P. R.	24083	Knight, R. D.	24103A
Court, T. D.	22070	Kolbo, L. A.	24139
Crum, D.	24093	Kostiner, M.	14048
Dant, G. B.	22073	Kralian, R. P.	14032
DeCuir, L. E.	22096A	Kristensen, K.	Sunnyvale
Derango, W. C.	20079	LaChapelle, F.	24061
Dexter, G. W.	24117	Laughlin, J.	20073
Disse, R. J.	24123	LaVine, J.	24081
Dobbs, G. H.	24094	Little, J. L.	24077
Dobrusky, W. B.	22119	Long, F.	24116
Donnelly, S.	22082	Lytton, J. G.	24082B
Ellis, R. C.	22078	Madrid, G. A.	22049
Emigh, G. A.	14032	Mahon, G. A.	22073
Ericksen, S. R.	24110	Marioni, J. D.	24074B
Felkins, J.	24034	Martin, W. P.	24089
Frey, R.	24049	McKeown, J.	24121
Foster, G. A.	14032	Michaelson, S. A.	14032
Franklin, A.	22079	Milanese, J. J.	24122
Franks, M. A.	25030	Munson, J. B.	24048
Frieden, H. J.	24071	Myers, G. L.	14056A
Gardner, S.	22053	Nelson, P. A.	24075
Gale, B.	22110	Ng, J.	22049
Greenwald, I. D.	24058A	Ngou, L.	25030
Griffith, E. L.	27029		

UNCLASSIFIED

System Development Corporation,
Santa Monica, California
PROPOSAL FOR VARIABLE FIELD
DEFINITION PSEUDO OPERATION IN
LARIi.
Scientific rept., TM-890/002/00,
by F. J. LaChapelle. 19 December 1962,
4p.
(Contract AF 19(628)-1648, Space Systems
Division Program, for Space Systems
Division, AFSC)

Unclassified report

DESCRIPTORS: Programming (Computers).
Satellite Networks.

UNCLASSIFIED

Reports that a Variable Field
Definition (VFD) pseudo will
generate one or more data words
made up of one or more subfields.
Also reports that the constituents
of a VFD pseudo operation will be
a VFD in the operation field and one
or more subfields in the M-term.
States that if a symbol appears in
the location field the tag will
be assigned to the location of the
first word generated.

UNCLASSIFIED

UNCLASSIFIED